



11390, Armand-Chaput Montréal, QC, Canada H1C 1S7  
Tél. : (514) 643-0800 Fax : (514) 643-0959  
Internet : [www.accocinema.com](http://www.accocinema.com)  
Licence # RBQ 2858-5883-23

## TECHNICAL SHEET

### Acoustic panels " BAFFLE "

- Construction : Two fibreglass board rigid of a density of  $96\text{kg/m}^3$  ( $6\text{lb/pi}^3$ ), 25 mm (1 inch) or 51 mm (2 inches) thick each. Both are laminated back to back and make a total thickness of 51 mm (2 inches) or 102 mm (4 inches)
- Covering : The acoustic panels will be covered with our standard fabrics from type n°1 or type n°2, color to be chosen from the architect. It will be glued to all surface with a minimum fold to the back of  $\pm 25$  mm. ( $\pm 1$  inch). The corners of the fabric will also be heat sealed to avoid fraying.
- Installation : The panels will be assembled with a perforated hanging system, installed at the factory on the top edge surface in sufficient quantity to ensure a solid suspension. The panels can then be hooked to the existing ceiling structures, with metal cables or chain supplied by the installator.
- The panels are warranty for 1 year.

### FLAMMABILITY:

ASTM E-84.....Class 1 or A

CAN/ULC-S102.....Passed

<sup>1</sup> Fasteners galvanized steel 20 gauge: 51 mm x 51 mm (2 inches x 2 inches)

<sup>2</sup> Fasteners galvanized steel 20 gauge: 51 mm x 125 mm (2 inches x 5 inches)